

SAFETY DATA SHEET



1. Identification

Product identifier **Key Fast Wax; Quart**

Other means of identification **KEY366-QT**
Product code

Recommended use **Paint Related Material**

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Keystone Automotive Industries
Address 5846 Crossings Blvd
Antioch, TN 37013

Telephone United States
TECH SUPPORT 877-539-4723
SALES

Website PHONE 615-781-5200
E-mail

Contact person www.LKQcorp.com
Emergency phone number jjatkinson@lkqcorp.com
Justin Atkinson
EMERGENCY 24 Hrs. 800-424-9300 ChemTrec

SECTION 2: HAZARDS IDENTIFICATION

Danger

Causes skin and eye irritation. Harmful if swallowed. Harmful if inhaled. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May cause damage to organs (liver, kidney, central nervous system) through prolonged or repeated exposure. Flammable liquid and vapor.

Wear protective gloves/eye protection. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Do not eat drink or smoke when using this product. Keep away from heat and open flames. Use explosion-proof equipment. Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists, get medical attention.

IF ON SKIN: Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation occurs, get medical attention.

IF SWALLOWED: Rinse mouth. Immediately call a doctor. Do NOT induce vomiting.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a doctor immediately if you feel unwell.

Call a doctor if you feel unwell.

IN CASE OF FIRE: Use dry chemical, water fog or carbon dioxide extinguisher for extinction.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of unused product and container in accordance with federal, state and local regulations.



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS #	WEIGHT %
Distillates (petroleum), hydro-treated light	64742-47-8	25-30**
Aluminum silicate	66402-68-4	3-8**
Polydimethylsiloxane	63148-62-9	1-5**
Mixed xylenes	1330-20-7	.25-3**

*Identity of this ingredient is a trade secret

**Exact percentage of this ingredient is a trade secret

SECTION 4: FIRST AID MEASURES

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

IF ON SKIN: Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation occurs, get medical attention.

IF SWALLOWED: Rinse mouth. Immediately call a doctor. Do NOT induce vomiting.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a doctor immediately if you feel unwell.

SECTION 5: FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water spray, dry chemical, carbon dioxide or "alcohol" foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion may produce noxious and irritating gases which will require fresh air source in fire fighting.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear as a general precaution.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Use personal protective equipment; see Section 8.

Keep product from entering storm sewers and ditches that may lead to waterways.

Stop spill at source; dike and contain large spills and transfer to recovery container. Use absorbent for small spills and containerize.

See Section 13 for disposal.

SECTION 7: HANDLING AND STORAGE

Handle according to good manufacturing and warehousing practices. Avoid contact with eyes, skin and clothing.

Store indoors between 40F/4C and 100F/38C

Use product only for intended use. Follow label directions.

Wash hands after handling.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT	CAS #	OSHA PEL (ppm or *mg.M ³) +=skin, c=ceiling	ACGIH TLV (ppm or *mg.M ³) +=skin, c=ceiling
Aluminum silicate	66402-68-4	5* resp 15* total	2* resp
Distillates (petroleum), hydro-treated light	64742-47-8	500	200
Mixed xylenes	1330-20-7	100	100

EYES: Wear eye protection (i.e. chemical safety glasses with side shields or goggles). Contact lenses should not be worn.

SKIN: Chemical resistant clothing (i.e. gloves) is recommended.

RESPIRATORY PROTECTION: Not expected to be needed. Where over-exposure through inhalation may occur from use, approved respiratory protection equipment is recommended.

VENTILATION: Local exhaust or general room ventilation is normally adequate.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash station is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Yellow opaque liquid
ODOR: Pina Colada fragrance
ODOR THRESHOLD: NA
pH: 8
MELTING/FREEZING POINT: Approx. 32F/0C
BOILING POINT: APPROX 212F/100C
BOILING RANGE: NA
FLASH POINT (CC): 105F/41C
EVAPORATION RATE: Approx. that of water
FLAMMABILITY: Flammable
UPPER/LOWER FLAMMABILITY LIMITS: NA
UPPER/LOWER EXPLOSIVE LIMITS: NA
VAPOR PRESSURE: NA
VAPOR DENSITY: NA
RELATIVE DENSITY: 7.9 LB/GAL
SOLUBILITY: Not water soluble
PARTITION COEFFICIENT: N-OCTANOL/WATER: NA
AUTO-IGNITION TEMPERATURE: NA
DECOMPOSITION TEMPERATURE: NA
VISCOSITY: Slightly viscous

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Stable
CHEMICAL STABILITY: Stable
POSSIBILITY OF HAZARDOUS REACTIONS: Low.
INCOMPATIBLE MATERIALS: Avoid oxidizers and reducers.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and other gases.

SECTION 11: TOXICOLOGICAL INFORMATION

This product contains no ingredients at or about 0.1% that are listed by NTP, IARC, or OSHA as carcinogens.

SECTION 12: ECOLOGICAL INFORMATION

Ecological data for this chemical mixture is not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local environmental regulations.

SECTION 14: TRANSPORT INFORMATION

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT	NA	NOT REGULATED WHEN SHIPPED BY GROUND	NA	NA	-	-

SECTION 15: REGULATORY INFORMATION

RTK Ingredients : Contains: Water (7732-18-5), Distillates (petroleum), hydro-treated light (64742-47-8), Aluminum silicate (66402-68-4), Polydimethylsiloxane (63148-62-9), Mixed xylenes (1330-20-7)

SECTION 16: OTHER INFORMATION

NFPA 704

HAZARD RATING

4=Severe H=1

3=Serious F=2

2=Moderate R=0

1=Slight

0=Minimal

Version 2.2 Revision Date: 11/22/2023

Disclaimer Keystone Automotive Industries cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used.

It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the

product, and to assume liability for loss, injury, damage or expense due to improper use. The

information in the sheet was written based on the best knowledge and experience currently available.