



SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet SBF5100-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/24/2017 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : SMART ULTRA-PREMIUM BODY FILLER
Product code : SBF5100

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Fillers

1.3. Supplier

FinishMaster, Inc.
115 W. Washington St.
Suite 700S
Indianapolis, IN 46204 - USA
T 317-237-3678

1.4. Emergency telephone number

Emergency number : INFOTRAC - 1-800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS Classification

| | |
|---|--|
| Skin corrosion/irritation Category 2 | Causes skin irritation |
| Serious eye damage/eye irritation Category 2 | Causes serious eye irritation |
| Carcinogenicity Category 2 | Suspected of causing cancer |
| Reproductive toxicity Category 2 | Suspected of damaging the unborn child. |
| Specific target organ toxicity (repeated exposure) Category 1 | Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation) |

2.2. GHS Label elements, including precautionary statements

GHS Labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
Suspected of damaging the unborn child.
Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS-US) : Do not breathe vapors, fume.
Wash hands thoroughly after handling.
Wear eye protection, protective clothing, protective gloves.
If exposed or concerned: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|-------------------------------------|----------------------|--------|--|
| styrene | (CAS-No.) 100-42-5 | 5 - 23 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 Repr. 2, H361 STOT RE 1, H372 |
| talc | (CAS-No.) 14807-96-6 | 5 - 23 | Carc. 2, H351 |
| titanium(IV) oxide | (CAS-No.) 13463-67-7 | < 5 | Carc. 2, H351 |
| ethylbenzene | (CAS-No.) 100-41-4 | < 5 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 |
| 2,2'-iminodiethanol, diethanolamine | (CAS-No.) 111-42-2 | < 5 | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Carc. 2, H351 STOT RE 2, H373 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe vapors, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapors, fume. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| styrene (100-42-5) | | |
|---|--|---|
| ACGIH | Local name | Styrene, monomer |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | ACGIH STEL (ppm) | 40 ppm |
| ACGIH | Remark (ACGIH) | CNS impair; URT irr; peripheral |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift | 600 ppm 5 mins. in any 3 hrs. |
| OSHA | Remark (OSHA) | (2) See Table Z-2. |
| OSHA | Regulatory reference (US-OSHA) | OSHA |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | | |
| ACGIH | Local name | Diethanolamine |
| ACGIH | ACGIH TWA (mg/m ³) | 1 mg/m ³ (Inhalable fraction and vapor) |
| ACGIH | Remark (ACGIH) | Liver & kidney dam |
| ACGIH | Regulatory reference | ACGIH 2018 |
| ethylbenzene (100-41-4) | | |
| ACGIH | Local name | Ethyl benzene |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | Remark (ACGIH) | URT irr; kidney dam (nephropathy) |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| OSHA | Regulatory reference (US-OSHA) | OSHA |
| talca (14807-96-6) | | |
| ACGIH | Local name | Talc (2009) Containing no asbestos fibers |
| ACGIH | ACGIH TWA (mg/m ³) | 2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica) 0.1 fibers/cm ³ (Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination) |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (ppm) | 20 mppcf |
| OSHA | Remark (OSHA) | Table Z-3. CAS No. source: eCFR Table Z-1. |
| OSHA | Regulatory reference (US-OSHA) | OSHA Annotated Table Z-3 Mineral Dusts |

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| titanium(IV) oxide (13463-67-7) | | |
|---------------------------------|-------------------------------------|--|
| ACGIH | Local name | Titanium dioxide |
| ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| ACGIH | Remark (ACGIH) | LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure) |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ |
| OSHA | Regulatory reference (US-OSHA) | OSHA |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Paste.
Color : light blue
Odor : aromatic
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : Not applicable
Boiling point : No data available
Flash point : 32 °C
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Non flammable.
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : Not applicable
Specific gravity / density : 1.11 - 1.15 g/cm³
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : Not applicable

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---------------------------|---------------------|
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : Not applicable |
| Viscosity, dynamic | : No data available |
| Explosion limits | : Not applicable |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2. Other information

| | |
|----------------------------|-------------------------|
| As Packaged Regulatory VOC | : 180 g/l (1.50 lb/gal) |
| As Applied Regulatory VOC | : 38 g/l (0.32 lb/gal) |

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| styrene (100-42-5) | |
|----------------------------|--|
| LD50 oral rat | > 6000 mg/kg body weight (Rat, Male, Weight of evidence, Oral) |
| LD50 dermal rat | > 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal) |
| LC50 inhalation rat (mg/l) | 11.8 mg/l air (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours)) |
| ATE US (gases) | 4500 ppmV/4h |
| ATE US (vapors) | 11 mg/l/4h |
| ATE US (dust, mist) | 1.5 mg/l/4h |

| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
|---|---|
| LD50 oral rat | 1600 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | 7640 mg/kg (Rabbit, Dermal) |
| ATE US (oral) | 620 mg/kg body weight |
| ATE US (dermal) | 7640 mg/kg body weight |

| ethylbenzene (100-41-4) | |
|--------------------------------|--|
| LD50 oral rat | 3500 mg/kg (Rat, Male/female, Experimental value, Oral) |
| LD50 dermal rabbit | 15432 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal) |
| LC50 inhalation rat (mg/l) | 17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours)) |
| ATE US (oral) | 3500 mg/kg body weight |
| ATE US (dermal) | 15432 mg/kg body weight |
| ATE US (gases) | 4500 ppmV/4h |
| ATE US (vapors) | 17.8 mg/l/4h |
| ATE US (dust, mist) | 1.5 mg/l/4h |

| titanium(IV) oxide (13463-67-7) | |
|--|---|
| LD50 oral rat | > 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s)) |
| LC50 inhalation rat (mg/l) | > 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s)) |

| | |
|-------------------------------|----------------------------------|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|-----------------------------------|--------------------------------|
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Suspected of causing cancer. |

| | |
|---|---|
| styrene (100-42-5) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | Reasonably anticipated to be Human Carcinogen |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| ethylbenzene (100-41-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| talc (14807-96-6) | |
| IARC group | 3 - Not classifiable, 2B - Possibly carcinogenic to humans |
| titanium(IV) oxide (13463-67-7) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| Reproductive toxicity | : Suspected of damaging the unborn child. |
| Specific target organ toxicity – single exposure | : Not classified |
| Specific target organ toxicity – repeated exposure | : Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation). |
| Aspiration hazard | : Not classified |
| Symptoms/effects after skin contact | : Irritation. |
| Symptoms/effects after eye contact | : Eye irritation. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|--|
| Ecology - general | : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. |
|-------------------|--|

| | |
|---|--|
| styrene (100-42-5) | |
| LC50 fish 1 | 10 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, GLP) |
| EC50 Daphnia 1 | 4.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, GLP) |
| ErC50 (algae) | 4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
| LC50 fish 1 | 1664 mg/l (96 h, Pimephales promelas, Static system) |
| EC50 Daphnia 1 | 55 mg/l (48 h, Daphnia magna) |
| ethylbenzene (100-41-4) | |
| LC50 fish 1 | 4.2 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Salmo gairdneri, Semi-static system, Fresh water, Experimental value) |
| EC50 Daphnia 1 | 1.8 - 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| talc (14807-96-6) | |
| LC50 fish 1 | > 100 g/l (24 h, Brachydanio rerio, Semi-static system) |
| titanium(IV) oxide (13463-67-7) | |
| LC50 fish 1 | > 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration) |
| ErC50 (algae) | 61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration) |

12.2. Persistence and degradability

| | |
|-------------------------------|--|
| styrene (100-42-5) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Chemical oxygen demand (COD) | 2.8 g O ₂ /g substance |
| ThOD | 3.07 g O ₂ /g substance |
| BOD (% of ThOD) | 0.42 (Literature study) |

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
|---|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0.22 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.52 g O ₂ /g substance |
| ThOD | 2.13 g O ₂ /g substance |
| BOD (% of ThOD) | 0.1 |
| ethylbenzene (100-41-4) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.44 g O ₂ /g substance (20d.) |
| Chemical oxygen demand (COD) | 2.1 g O ₂ /g substance |
| ThOD | 3.17 g O ₂ /g substance |
| talc (14807-96-6) | |
| Persistence and degradability | Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |
| titanium(IV) oxide (13463-67-7) | |
| Persistence and degradability | Biodegradability: not applicable. |
| Biochemical oxygen demand (BOD) | Not applicable (inorganic) |
| Chemical oxygen demand (COD) | Not applicable (inorganic) |
| ThOD | Not applicable (inorganic) |

12.3. Bioaccumulative potential

| styrene (100-42-5) | |
|---|---|
| BCF fish 1 | 35.5 (Carassius auratus, Literature study) |
| Log Pow | 2.96 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
| Log Pow | -2.18 - -1.43 (Experimental value) |
| Bioaccumulative potential | Not bioaccumulative. |
| ethylbenzene (100-41-4) | |
| BCF fish 1 | 1 - 2.4 (Other, 6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value) |
| Log Pow | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |
| titanium(IV) oxide (13463-67-7) | |
| Bioaccumulative potential | Not bioaccumulative. |

12.4. Mobility in soil

| styrene (100-42-5) | |
|--|--|
| Surface tension | 0.032 N/m (20 °C) |
| Log Koc | 2.55 (log Koc, Estimated value) |
| Ecology - soil | Low potential for adsorption in soil. |
| ethylbenzene (100-41-4) | |
| Surface tension | 0.071 N/m (23 °C, 0.0582 g/l, EU Method A.5: Surface tension) |
| Log Koc | 2.71 (log Koc, PCKOCWIN v1.66, QSAR) |
| Ecology - soil | Low potential for adsorption in soil. Toxic to soil organisms. |
| titanium(IV) oxide (13463-67-7) | |
| Ecology - soil | Low potential for mobility in soil. |

12.5. Other adverse effects

No additional information available

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|---|---------|
| styrene (100-42-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Subject to reporting requirements of United States SARA Section 313 | |
| Listed on EPA Hazardous Air Pollutant (HAPS) | |
| CERCLA RQ | 1000 lb |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Subject to reporting requirements of United States SARA Section 313 | |
| Listed on EPA Hazardous Air Pollutant (HAPS) | |
| CERCLA RQ | 100 lb |
| ethylbenzene (100-41-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Subject to reporting requirements of United States SARA Section 313 | |
| Listed on EPA Hazardous Air Pollutant (HAPS) | |
| CERCLA RQ | 1000 lb |
| talc (14807-96-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| titanium(IV) oxide (13463-67-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

15.2. International regulations

CANADA

| | |
|---|--|
| styrene (100-42-5) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| ethylbenzene (100-41-4) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| talc (14807-96-6) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| titanium(IV) oxide (13463-67-7) | |
| Listed on the Canadian DSL (Domestic Substances List) | |

EU-Regulations

No additional information available

National regulations

SMART ULTRA-PREMIUM BODY FILLER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| |
|---|
| styrene (100-42-5) |
| Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program) Listed on EPA Hazardous Air Pollutant (HAPS) |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) |
| Listed on IARC (International Agency for Research on Cancer) Listed on EPA Hazardous Air Pollutant (HAPS) |
| ethylbenzene (100-41-4) |
| Listed on IARC (International Agency for Research on Cancer) Listed on EPA Hazardous Air Pollutant (HAPS) |
| titanium(IV) oxide (13463-67-7) |
| Listed on IARC (International Agency for Research on Cancer) |

15.3. US State regulations

| styrene (100-42-5) | | | | | |
|---|---|---|---|----------------------------------|-------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| Yes | No | No | No | | |
| 2,2'-iminodiethanol, diethanolamine (111-42-2) | | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| Yes | No | No | No | | |
| ethylbenzene (100-41-4) | | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
| Yes | No | No | No | 54 µg/day | |

SECTION 16: Other information

| Full text of H-phrases: | |
|-------------------------|---|
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H302 | Harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H351 | Suspected of causing cancer |
| H361 | Suspected of damaging fertility or the unborn child |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H373 | May cause damage to organs through prolonged or repeated exposure |

SDS US GHS (GHS HazCom2012)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. FinishMaster makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. FinishMaster cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above FinishMaster's recommendations for use, may substantially alter the composition and hazards of the product. FinishMaster data sheets are available via the FinishMaster website at WWW.FINISHMASTER.COM.