

1. Identification

Product identifier	Key Kondition Vinyl Dressing; Ga		
Other means of identification	KEY244-G		
Product code			
Recommended use	Paint Related Material		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer	Keystone Automotive Industries		
Company name	5846 Crossings Blvd		
Address	Antioch, TN 37013		
	United States		
	TECH SUPPORT	877-539-4723	
Telephone	SALES		
	PHONE	615-781-5200	
Website	www.LKQcorp.com		
E-mail	jjatkinson@lkqcorp.com		
Contact person	Justin Atkinson		
Emergency phone number	EMERGENCY 24 Hrs.	800-424-9300 ChemTrec	

SECTION 2: HAZARDS IDENTIFICATION

Danger

Causes skin and eye irritation. Harmful if swallowed. Harmful if inhaled.. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Flammable liquid and vapor.

Wear protective gloves/eye protection. Avoid breathing vapors. Use only outdoors or in a well ventilated area. Do not eat drink or smoke when using this product. Keep away from heat and open flames. Use explosion proof equipment. Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention

IF ON SKIN: Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation occurs, get medical attention.

IF SWALLOWED: Rinse mouth. Immediately call a doctor. Do NOT induce vomiting.

IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a doctor immediately if you feel unwell.

IN CASE OF FIRE: Use dry chemical or carbon dioxide extinguisher for extinction.

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with federal, state and local regulati



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS #	WEIGHT %
Aliphatic hydrocarbon	8052 41 3	65 75**
Polyether polyol	025322 69 4	25 35**

*Identity of this ingredient is a trade secret

**Exact percentage of this ingredient is a trade secret

SECTION 2: HAZARDS IDENTIFICATION

Danger
Causes skin and eye irritation. Harmful if swallowed. Harmful if inhaled.. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Flammable liquid and vapor.

Wear protective gloves/eye protection. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Do not eat drink or smoke when using this product. Keep away from heat and open flames. Use explosion-proof equipment. Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

IF ON SKIN: Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation occurs, get medical attention.

IF SWALLOWED: Rinse mouth. Immediately call a doctor. Do NOT induce vomiting.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a doctor immediately if you feel unwell.

IN CASE OF FIRE: Use dry chemical or carbon dioxide extinguisher for extinction.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with federal, state and local regulati

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS #	WEIGHT %
Aliphatic hydrocarbon	8052-41-3	65-75**
Polyether polyol	025322-69-4	25-35**

*Identity of this ingredient is a trade secret
**Exact percentage of this ingredient is a trade secret

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT	CAS #	OSHA PEL (ppm or *mg.M ³) +=skin, c=ceiling	ACGIH TLV (ppm or *mg.M ³) +=skin, c=ceiling
Aliphatic Hydrocarbon	8052-41-3	100	100

EYES: Wear eye protection (i.e. chemical safety glasses with side shields or goggles). Contact lenses should not be worn.

SKIN: Chemical resistant clothing (i.e. gloves) is recommended.

RESPIRATORY PROTECTION: Not expected to be needed. Where over-exposure through inhalation may occur from use, approved respiratory protection equipment is recommended.

VENTILATION: Local exhaust or general room ventilation is normally adequate.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash station is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Purple liquid

ODOR: Grape fragrance

ODOR THRESHOLD: NA

pH: NA

MELTING/FREEZING POINT: NA

BOILING POINT: APPROX 315F/157C

BOILING RANGE: NA

FLASH POINT (CC): 105F/41C

EVAPORATION RATE: NA

FLAMMABILITY: Flammable

UPPER/LOWER FLAMMABILITY LIMITS: NA

UPPER/LOWER EXPLOSIVE LIMITS: 6%/1% (Aliphatic hydrocarbon)

VAPOR PRESSURE: NA

VAPOR DENSITY: 4.9 (Air = 1)

RELATIVE DENSITY: 7.0 LB/GAL

SOLUBILITY: Soluble in hydrocarbon solvents Not soluble in water

PARTITION COEFFICIENT: N-OCTANOL/WATER: NA

AUTO-IGNITION TEMPERATURE: NA

DECOMPOSITION TEMPERATURE: NA

VISCOSITY: Water thin

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: Stable

CHEMICAL STABILITY: Stable

POSSIBILITY OF HAZARDOUS REACTIONS: Low.

INCOMPATIBLE MATERIALS: Avoid oxidizers and reducers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and other gases.

SECTION 11: TOXICOLOGICAL INFORMATION

This product contains no ingredients at or about 0.1% that are listed by NTP, IARC, or OSHA as carcinogens.

SECTION 12: ECOLOGICAL INFORMATION

Ecological data for this chemical mixture is not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state and local environmental regulations.

SECTION 14: TRANSPORT INFORMATION

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT		Not regulated when shipped by land			-	-
DOT	UN1268	Petroleum Distillates, N.O.S (Naptha Solvent)	3	PGIII		Shipped by plane or boat

SECTION 15: REGULATORY INFORMATION

RTK Ingredients : Aliphatic hydrocarbon (8052-41-3), Polyether polyol (025322-69-4)

SECTION 16: OTHER INFORMATION

NFPA 704

HAZARD RATING

4=Severe H=Health H=1
3=Serious F=Fire F=2
2=Moderate R=Reactivity R=0
1=Slight
0=Minimal

Version 2.2 Revision Date: 11/22/2023

Disclaimer Keystone Automotive Industries cannot anticipate all conditions under which this information and

its product, or the products of other manufacturers in combination with its product, may be used.

It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the

product, and to assume liability for loss, injury, damage or expense due to improper use. The

information in the sheet was written based on the best knowledge and experience currently available.